

Contractor, Lawn & Garden, and Party Equipment Rentals 1829 White Bear Ave. - Maplewood, MN 55109

Phone: 651-770-3841 – Fax: 651-770-1725 www.heinvrental.com

MORTAR MIXER INSTRUCTIONS

Towing

- 1. Do not tow the mixer unless the towpole is bolted in place and safety bolt on end of towpole is securely fastened.
- 2. Securely fasten hitch to towing vehicle.
- 3. Safety chains must cross under towpole and be positioned to prevent the towpole from dropping to the ground in event of a hitch failure.
- 4. Lock the drum in tow position.
- 5. Never tow the mixer over 55 MPH! Do not tow unless mixing drum is empty!

Starting

- 1. Be sure the belt slip lever is in the "START\STOP" position.
- 2. Check to see that drum is clear of any obstacles and drum gate is closed.
- 3. Start engine and allow to warm up for 1-2 minutes.
- 4. Close engine cover and latch both sides before putting belt slip lever in the "MIX" position.

Charging the Mixer

- 1. Place the ingredients into the drum in the following order, AFTER ENGAGING PADDLES:
- A. Half of required water.
- B. Half of required sand.
- C. Required mortar cement or plaster.
- D. Balance of water.
- E. Balance of sand.
- 2. After discharging batch, immediately add half of required water for next batch and let paddles turn in water a short time. This will keep both drum and paddles clean and prevent lumps in mix.
- 3. When finished thoroughly clean the mixer. You will be charged a cleaning charge if machine is not cleaned before return!

Stopping the Mixer

- 1. Put belt slip lever in" START/STOP" position.
- 2. Push STOP button on engine cover till engine stops.