

Hejny Rentals, Inc.

Contractor, Lawn & Garden, and Party Equipment Rentals
1829 White Bear Ave. - Maplewood, MN 55109
Phone: 651-770-3841 – Fax: 651-770-1725
www.hejnyrental.com

Powder Actuated Tool (Stud Gun)

Hilti Model #DX36M

WARNING: To reduce the likelihood of injury, always follow these instructions.

1. Never use tool unless you have received proper instructions on its safe use.
2. Always inspect tool for proper operation before use. Inspect the tool to ensure the parts are in safe condition for use. Do not use tool that is incomplete or does not operate properly.
3. The operator and all bystanders must wear eye protection meeting the requirements of ANSI Z87.1 and a hard hat while tool is in use.
4. Wear ear protection when working in confined areas.
5. Always use genuine Hilti fasteners, cartridges and spare parts!
6. Use the stabilizer whenever possible (see tool operator's manual for details). This will help you keep the tool perpendicular to the work surface; and help restrain any free-flying materials.
7. Hold the tool perpendicular to work surface when making a fastening - this will reduce the possibility of any ricocheting off the work surface.
8. Keep your arms flexed when operating the tool (do not stiff arm). If you feel any pain or discomfort, discontinue use.
9. Make sure the base material is suitable for powder actuated fastening. Materials that are too hard (e.g. welded steel, cast iron), too soft (e.g. wood, drywall), or too brittle (e.g. tile, glass), can easily cause the fastener to shatter or free-flight.
10. When fastening into concrete, never fasten closer than 2" from the edge. Fastening too close to the edge not only can reduce the holding value, but can also cause the concrete to split and the fastener to free-flight.
11. Never fasten through an existing hole, except as recommended by Hilti. Misalignment with the existing hole could cause the fastener to shatter or ricochet.
12. Never re-drive a fastener - this could cause the fastener to shatter.
13. IF CARTRIDGE FAILS TO IGNITE WHEN THE TOOL IS ACTUATED FOLLOW THE FOLLOWING INSTRUCTIONS: Note: Once the magazine/cartridge is removed, dispose of it in such a way that it can neither be used again nor misused.
 - A. Keep the tool pressed against the work surface for 30 seconds.
 - B. Withdraw tool from work surface, taking care that the tool is not pointed at anyone.
 - C. For magazine tools: advance the cartridge strip manually, and continue to use the remaining cartridges in the strip.
14. Never attempt to pry a cartridge from the magazine strip or from the tool - this can cause the cartridge to ignite.
15. Keep the tool and cartridges locked in a container and in a safe place when not in use. Keep out of reach of children.
16. Never point the tool at yourself or anyone else!
17. Never cock or depress the tool against your hand or other part of your body!
18. Do not make fastenings in an explosive or flammable atmosphere.
19. If you need assistance or have a question regarding a Hilti product, contact Hilti at: 1-800-879-8000

Need It. Rent It!