

Hejny Rentals, Inc.

Contractor, Lawn & Garden, and Party Equipment Rentals
1829 White Bear Ave. - Maplewood, MN 55109
Phone: 651-770-3841 – Fax: 651-770-1725
www.hejnyrental.com

Primatech H330 Ratcheting Floor Nailer

Note: Nailer is designed to be used to nail 3/4" tongue and groove flooring through the TONGUE.

Operation of the Primatech 330 Nailer

Using the rubber capped mallet that is provided with your nailer, tap the flooring in place.

Strike the nailer plunger with the RUBBER END of the mallet to drive the cleat. The Primatech 330 is designed to be struck several times in order to countersink the nail.

The nailer must be held firmly, flat on the surface of the hardwood floor and hit repeatedly until the plunger returns to its upright position.

Hardwood Floor Installation

1. With an expansion space, drill the face of the flooring and use finishing nails for the first row. Use a nail set to countersink the nails and fill the hole with matching putty.
2. For the first few rows, drill at a 45 degree angle at the tongue and use finishing nails.
3. Using the Primatech 330 multiple hit nailer, fix the flooring at the 45 degree pre-determined angle. Nail 3" from the ends and every 10-12".
4. At the other end when it is no longer possible to use the nailer, repeat the procedure in #1 and #2 for the last rows.

Hints

Take particular attention when striking the nailer. Make sure that it seats firmly on the hardwood floor by applying a vertical pressure to keep it well seated on the floor. Sometimes, while striking the nailer, the hand holding the nailer has a tendency of lifting the front of the nailer for a moment. This causes the nail to bend as the nailer moves during the stroke. To prevent this, you may lean you foot on the base.

Need It. Rent It!