

# Hejny Rentals, Inc.

Contractor, Lawn & Garden, and Party Equipment Rentals  
1829 White Bear Ave. - Maplewood, MN 55109  
Phone: 651-770-3841 – Fax: 651-770-1725  
[www.hejnyrental.com](http://www.hejnyrental.com)

## DUMP TRAILERS

**ALL TRAILERS HAVE A 100 MILE RESTRICTION FROM HEJNY RENTALS, INC.**

### HOOK-UP

1. Bumper or clamp hitches are not acceptable.
2. If towing with a permanent or "frame" hitch, check bolts for tightness.  
Insure that a proper size ball is used.
  - #3000 Dump Trailer requires a 2" ball and a 5000 lb. hitch
  - #7000 Dump Trailer requires a 2 5/16" ball or pintle hitch, electric brakes, and a 10,000 lb. hitch.
3. With trailer wheels chocked to prevent rolling, raise the front end of the trailer coupler directly over the hitch ball, then lower it until it is seated on the hitch ball, covering it completely.
4. Check under the coupling to ensure the ball clamp is below the ball and not riding on top of it.
5. Make sure jack is fully raised.
6. Attach the safety chains so they cross underneath the trailer tongue.
7. Check the light wires to make sure they are good condition and have enough slack to allow for turning. Be sure that the brake, turning, and running lights are operational.

### LOADING

1. ASPHALT CAN ONLY BE HAULED IF TRAILER IS RETURNED CLEAN OR THERE WILL BE \$50 CLEANING CHARGE!
2. CUSTOMER WILL BE CHARGED \$50 FOR CLEANING IF APPLICABLE!
3. Caution must be used in loading your trailer in order not to exceed the gross vehicle weight rating of your trailer or tow vehicle. Gravel, sand, and soil are approx. 2,700 lbs. per cubic yard, which should be taken into consideration when loading these items. Normal weight distribution of a trailer is approx. 10% of load on the tongue. Too much weight on the tongue will overload the tow vehicle hitch. Too little tongue weight could cause the trailer to sway.
4. DO NOT OVERLOAD TRAILER
5. Use the heaviest possible vehicle for towing. A loaded trailer should be NEVER outweigh the towing vehicle!
6. Load the trailer so that 60% of the load is forward of the wheels. Many trailers have the balance point marked. Secure and cover all loads as necessary.

### TOWING

1. Start slowly, drive slowly, stop slowly - you are towing extra weight.
2. Stop immediately if the trailer sways. Determine the cause of the sway; whether it be improper loading, load shifting, loose hitch, tire pressure, or broken springs, etc.
3. Be careful when backing up - use a spotter.
4. When passing or parking, remember the extra length of your trailer.
5. With heavy loads be careful going down grades.
6. DO NOT transport passengers on/in a towed trailer.

**ATTENTION: This trailer is equipped with a trickle charger and must be plugged into an extension cord during non-use!**

**WARNING! This trailer cannot be transferred or towed by a different vehicle!**

Description of material or equipment being hauled: \_\_\_\_\_

**Need It. Rent It!**